

# UNIVERSAL ISS 165

## 2-way component kit



• Butyl surround  
**Perfect reliability**

• Phase plug  
**Better dispersion**

• Polyglass cone  
**Neutral sound without coloration**

• Integrated crossover  
(woofer + tweeter)  
**Easy installation**

• Processed aluminum inverted dome tweeter  
**Smoothness and definition without directivity**  
• Partial horn loading  
**Best positioning in the soundstage**

## ADVANTAGES


- High sensitivity
- Shallow mounting depth (49.9 mm)
- Partial horn loading tweeter
- Dynamics and neutrality
- 2 tweeter support types
- Tweeter compact size



Removable tweeter



Tilted mounting  
Easy installation



Assembly options:  
car and display

## TECHNICAL CHARACTERISTICS

**Woofer:** 6<sup>1</sup>/<sub>2</sub>" (165mm)

**Voice-coil diameter:** 1" (25mm)

**Voice-coil height:** 0<sup>1</sup>/<sub>4</sub>" (7mm)

**Magnet:** 3<sup>9</sup>/<sub>16</sub>" (90mm)

**Processed Aluminum inverted dome tweeter**

**Integrated crossover:** 6dB/oct (woofer + tweeter)

**Max. power:** 140W

**Nom. power:** 70W rms

**Sensitivity (2,83 V/1 m):** 92.6dB

**Frequency response:** 60Hz – 20kHz

**Accessories:** Supplied without grille

 **Integration**  
INSTANT GRATIFICATION

 **FOCAL**<sup>®</sup>  
THE SPIRIT OF SOUND