



S12L72-11

**Dual Voice Coil
Subwoofer 30 cm**

Power Handling

750 Watts RMS / 1500 Watts Max.

Technical Specifications

Impedance	Zn	2 x 2 Ohms
Voice Coil Diameter	Ø	61 mm
Max. Linear Excursion	Xmax	+/- 14 mm
Cone Area	Sd	645 cm ²
Moving Mass	Mms	247,3 g
DC Resistance	Re	Ohms
Resonance Frequency	Fs	34,9 Hz
Mechanical Q-Factor	Qms	6,26
Electrical Q-Factor	Qes	0,51
Total Q-Factor	Qts	0,5
Equivalent Air Volume	VAS	45,6 L
VC Inductance	Le	mH
Flux Density	B/L	18,264 N/A
Efficiency 1W/1m	SPL	87,3 dB

Recommended Enclosure

Ported Box	
Vented Volume:	71 L
Port Area:	217 cm ²
Port Length:	42 cm

Recommended Enclosure

Ported Box	
Vented Volume:	49,6 L
Port Area:	217 cm ²
Port Length:	57 cm

Mechanical Components

- Diecast Aluminium Basket
- Polypropylene Cone
- Santoprene Surround
- Polypropylene Dustcap
- Single Spider
- Polyimide Voice Coil Former

Dimensions & Weight

External Diameter:	321 mm
Mounting Diameter:	281 mm
Mounting Depth:	173 mm
Shipping Weight:	11,7 kg

